Datasheet Revo BOW

For more informations visit www.corratec.de



TECHNOLOGIES



DESCRIPTION

- Entry level with robust Revo BOW carbon frame.
- Arched top tube for increased safety and comfort on tech- nical trails.
- Sram Level 2-piston brakes for safe descents.

FRAME

EQUIPMENT

MAIN:

Corratec BOW SL Carbon 29" 12x148mm FRAME: FORK: MANITOU MARKHOR 29" 15x110 100mm BRAKES: SRAM LEVEL ULTIMATE STEALTH 2-Piston 180 mm front SRAM LEVEL T 2-Piston 160mm rear

STEM: ALLOY 31.8mm 80-90mm -10 Deg

HANDLEBAR: ALLOY 31.8mm 760mm 9 Deg Backweep 20m

m Rise

SADDLE: SELLE ITALIA MODEL X

ALLOY TWIN BOLT 31.6x400mm SEATPOST:

WHEELSET:

622-23 15x110 6Bolt front 622-23 12x148mm 6Bolt rear RIM:

Schwalbe Nobby Nic Performance Addix 57-62

2 front Schwalbe Nobby Nic Performance Addix 57-62

DRIVE:

CHAINWHEEL: CASSETTE: REAR DERAILLEUR:

SRAM SX EAGLE DUB 175mm 32T SRAM PG1210 EAGLE 11-50T 12-SPEED

SRAM SX EAGLE 12-SPEED

SRAM SX EAGLE 1x12-SPEED

SPECIAL:

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications. Rendering is for reference only.