



Datasheet E-Power iLink 180 Factory

For more informations visit www.corratec.de

iLINK 180

E-Power iLink 180 Factory

Frame: Corratec E-Power iLink 180 Boost

Components: Sram GX AXS Eagle

Size: 42, 48, 52

Colors:



TECHNOLOGIES



DESCRIPTION

- Ultralight carbon frame including carbon - rear triangle with 180mm travel.
- A downhill machine that ensures amazing pleasure on all trails of the world.
- Shadow Edge Tube 3.0 - worldwide most stable and safest corratec E-Bike frame.

FRAME

CM	A	B	C	D	E	F	G	H
42	599	86	65	77	1236	445	455	616
48	611	97	65	77	1248	445	465	621
52	623	106	65	77	1262	445	475	629

EQUIPMENT

MAIN:

FRAME:	Corratec E-Power iLink 180 Boost
FORK:	Rockshox FS Zeb Ultimate RC2 29" Boost
FULLY DAMPER:	Rockshox Super Deluxe Ultimate
BRAKES:	SRAM G2 front SRAM G2 RSC rear
STEM:	ZZYZX SL Alloy
HANDLEBAR:	ZZYZX SL Alloy Handlebar
SADDLE:	Selle San Marco Gnd Full-fit
SEATPOST:	Rockshox Reverb AXS

DRIVE:

CHAINWHEEL:	SRAM X-SYNC 2 34T
CASSETTE:	SRAM Eagle Black 10-50
REAR DERAILLEUR:	SRAM AXS Eagle
SHIFT LEVERS:	SRAM GX AXS Eagle

WHEELSET:

RIM:	Mavic E-Deemax S30 front Mavic E-Deemax S35 rear
TIRE:	Michelin E-Wild 29 front Michelin E-Wild 650B rear

SPECIAL:

CHAINWHEEL RATIO:	1s; 34
CASSETTE RATIO:	12s; 10 12 14 16 18 21 24 28 32 36 42 50
FORK SUSPENSION TRAVEL:	180 mm
SIZE BRAKE DISC:	203 mm front 203 mm rear
ENGINE:	BOSCH Performance CX Race
BATTERY:	BOSCH PowerTube 625Wh
ACCESOIRES:	Bosch Kiox 300 Display

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications.

Rendering is for Reference only.