Datasheet E-Power Trekking 28 P5 8S Wave

For more informations visit www.corratec.de



TECHNOLOGIES



DESCRIPTION

- The high-quality aluminum frame offers the highest security and stability.
- The newly developed Trinity Tube Edge with its three chamber system is designed for maximum stability and safety.

Corratec E-Power Trekking Trinity Tube 28 Wa

Low entry and the ergonomic design enable comfortable riding.

FRAME

СМ	Α	В	c	D	E	F	G	н	
45	620	175	69	74	1189	490	425	659	
50	630	185	69	74	1200	490	432	669	
55	640	195	69	74	1211	490	439	678	

ve

Suntour NEX-E25P 700C

ZZYZX Trekking Handlebar

Shimano MT 200 front Shimano MT200 rear ZZYZX SL Alloy Stem

ZZYZX Alloy Seatpost

EQUIPMENT

MAIN:

FRAME:

FORK: BRAKES: STEM: HANDLEBAR: SEATPOST:

WHEELSET:

RIM:	ZZYZX Trekking 29er Disc front ZZYZX Trekking 29er Disc rear
TIRE:	Schwalbe Energizer Active Plus front Schwalbe Energizer Active Plus rear

DRIVE:

CHAINWHEEL: CASSETTE: SHIFT LEVERS:

ZZYZX E-Power Crank 38T Shimano Nexus Shimano NEXUS Revo Shifter

SPECIAL:

CHAINWHEEL RATIO:
CASSETTE RATIO:
FORK SUSPENSION TRAVEL:
SIZE BRAKE DISC
ENGINE:
BATTERY:
LIGHTS:
REAR CARRIER:

8s; 19 63 mm

1s; 38

180 mm front 160 mm rear BOSCH Performance Line BOSCH Power Tube 500 Wh AXA Compact Line 20 Massload MIK System Direct Mount Carrier

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.

Rendering is for Reference only.