Datasheet E-Power Trekking 28 P6 8S Wave

For more informations visit www.corratec.de



TECHNOLOGIES



DESCRIPTION

- The high-quality aluminum frame offers the highest security and stability.
- The newly developed Trinity Tube Edge with its three chamber system is designed for maximum stability and safety.
- Low entry and the ergonomic design enable comfortable riding.

FRAME									
	СМ	Α	в	c	D	Е	F	G	н
	45	620	175	69	74	1189	490	425	659
	50	630	185	69	74	1200	490	432	669
	55	640	195	69	74	1211	490	439	678

EQUIPMENT

MAIN:		DRIVE:	
FRAME:	Corratec E-Power Trekking Trinity Tube 28 Wa ve	CASSETTE: SHIFT	Shimano Nexus Shimano NEXUS Revo Shifter
FORK:	Suntour NEX-E25P 700C	LEVERS:	
BRAKES:	Shimano MT 200 front Shimano MT200 rear		
STEM:	ZZYZX SL Alloy Stem		
HANDLEBAR:	ZZYZX Trekking Handlebar		
SEATPOST:	ZZYZX Alloy Seatpost		
WHEELSET:		SPECIAL:	
RIM:	ZZYZX Trekking 29er Disc front ZZYZX Trekking 29er Disc rear	CASSETTE RATIO:	8s; 19
TIRE:	Schwalbe Energizer Active Plus front	FORK SUSPENSION TRAVEL:	63 mm
	Schwalbe Energizer Active Plus rear	SIZE BRAKE DISC	180 mm front 160 mm rear
		ENGINE:	BOSCH Performance Line
		BATTERY:	BOSCH PowerTube 625Wh
		LIGHTS:	Trelock LS230 VEO 20
		REAR CARRIER:	Massload MIK System Direct Mount Carrier

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.

Rendering is for Reference only.