



# Datasheet Revolution iLink Pro

For more informations visit [www.corratec.de](http://www.corratec.de)

## Revolution iLink Pro

Frame: Corratec Revolution iLink

Components: Shimano Deore XT 12S

Size: 44, 48, 52

Colors:



### TECHNOLOGIES



### DESCRIPTION

- Outstanding **Inside Link Technology** for a tight rear angle at any time without lockout.
- The perfect device for long **Allmountain tours and crossing the Alps**.
- **Frame with Boost standard** - light and stiff at the same time.

### FRAME

CM	A	B	C	D	E	F	G	H
44	589	101	68	75	1144	435	445	610
48	616	108	68	75	1171	435	460	615
52	632	124	68	75	1192	435	475	630

### EQUIPMENT

#### MAIN:

FRAME:	<b>Corratec Revolution iLink</b>
FORK:	<b>Rockshox SID RL 29" Boost</b>
FULLY DAMPER:	<b>Rockshox Deluxe Select</b>
BRAKES:	<b>Shimano Deore XT front</b> <b>Shimano Deore XT rear</b>
STEM:	<b>ZZYZX SL Alloy</b>
HANDLEBAR:	<b>ZZYZX SL Alloy Handlebar</b>
SADDLE:	<b>Selle Italia Model X</b>
SEATPOST:	<b>Kindshock RAGEi</b>

#### DRIVE:

CHAINWHEEL:	<b>Shimano Deore XT</b>
CASSETTE:	<b>SRAM CS PG1230 11-50T</b>
REAR DERAILLEUR:	<b>Shimano DEORE XT SGS 12S</b>
SHIFT LEVERS:	<b>Shimano Deore XT</b>

#### WHEELSET:

RIM:	<b>DT Swiss M 1900 Spline 29 front</b> <b>DT Swiss M 1900 Spline 29 rear</b>
TIRE:	<b>Schwalbe Nobby Nic front</b> <b>Schwalbe Nobby Nic rear</b>

#### SPECIAL:

CHAINWHEEL RATIO:	<b>1s; 32</b>
CASSETTE RATIO:	<b>12s; 10 12 14 16 18 21 24 28 33 39 45 51</b>
FORK SUSPENSION TRAVEL:	<b>120 mm</b>
SIZE BRAKE DISC:	<b>180 mm front</b> <b>180 mm rear</b>

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.