



# Datasheet Revolution iLink Pro

For more informations visit [www.corratec.de](http://www.corratec.de)

R  
iLink

## Revolution iLink Pro

Frame: Corratec Revolution iLink SL

Components: Shimano Deore XT 12S

Size: 44, 48, 52

Colors:



### TECHNOLOGIES



### DESCRIPTION

- The perfect bike for allmountain tours and flowy trails.
- iLink TECHNOLOGY – the rear triangle without a separate lockout achieves maximum propulsion.
- The bike, developed according to the Boost standard, generates maximum agility off-road.

### FRAME

### EQUIPMENT

#### MAIN:

FRAME:	<b>Corratec Revolution iLink SL</b>
FORK:	<b>Rockshox SID RL 29" Boost</b>
FULLY DAMPER:	<b>Rockshox Deluxe Select</b>
BRAKES:	<b>Shimano Deore XT front</b> <b>Shimano Deore XT rear</b>
STEM:	<b>ZZYZX SL Alloy Stem</b>
HANDLEBAR:	<b>ZZYZX SL Alloy Handlebar</b>
SADDLE:	<b>Selle Italia Model X</b>
SEATPOST:	<b>Kindshock RAGEi</b>

#### DRIVE:

CHAINWHEEL:	<b>Shimano Deore XT</b>
CASSETTE:	<b>Shimano SLX 12S</b>
REAR DERAILEUR:	<b>Shimano DEORE XT SGS 12S</b>
SHIFT LEVERS:	<b>Shimano Deore XT</b>

#### WHEELSET:

RIM:	<b>DT Swiss M 1900 Spline 29 front</b> <b>DT Swiss M 1900 Spline 29 rear</b>
TIRE:	<b>Schwalbe Hans Dampf 60-622 front</b> <b>Schwalbe Hans Dampf 60-622 rear</b>

#### SPECIAL:

CHAINWHEEL RATIO:	<b>1s; 32</b>
CASSETTE RATIO:	<b>12s; 10 12 14 16 18 21 24 28 33 39 45 51</b>
FORK SUSPENSION TRAVEL:	<b>120 mm</b>
SIZE BRAKE DISC:	<b>180 mm front</b> <b>160 mm rear</b>

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications.

Rendering is for reference only.