



Datasheet E-Power iLink 180 Race

For more informations visit www.corratec.de

iLINK 180

E-Power iLink 180 Race

Frame: Corratec E-Power iLink 180
Components: Bosch Performance Line CX
Size: 42, 48, 52
Colors:



The rendering is for reference only

TECHNOLOGIES



DESCRIPTION

- **Luxury carbon frame** with 180mm travel.
- **Shadow Edge Tube 2.0** - worldwide most stable and safest corratec E-Bike frame.
- **Inside Link Technology** goes E-MTB.
- **Highest Stiffness** at minimum weight.
- **85 NM** maximum performance.
- **625 WH** maximum range.

FRAME

CM	A	B	C	D	E	F	G	H
42	599	86	65	77	1236	445	455	616
48	611	97	65	77	1248	445	465	621
52	623	106	65	77	1262	445	475	629

EQUIPMENT

MAIN:

FRAME: **Corratec E-Power iLink 180**
 FORK: **Rockshox Yari Motion Control RC 29" Boost**
 FULLY DAMPER: **Rockshox Super Deluxe**
 BRAKES: **Magura MT Thirty front**
Magura MT Thirty rear
 STEM: **ZZYZX SL Alloy**
 HANDLEBAR: **ZZYZX SL Alloy Handlebar**
 SADDLE: **Selle Italia Model X**
 SEATPOST: **Kindshock 900i**

DRIVE:

CHAINWHEEL: **SRAM X-SYNC 2 34T**
 CASSETTE: **SRAM CS PG1210 11-50T**
 REAR DERAILLEUR: **SRAM GX Eagle Lunar 12S**
 SHIFT LEVERS: **SRAM SX Eagle Single Click E Trigger**

WHEELSET:

RIM: **ZZYZX Cross Attack 29 Boost front**
ZZYZX Cross Attack 650B rear
 TIRE: **Michelin Wild Enduro TLR 29 front**
Michelin Wild Enduro TLR 650B+ rear

SPECIAL:

CHAINWHEEL RATIO: **1s; 34**
 CASSETTE RATIO: **12s; 10 12 14 16 18 21 24 28 32 36 42 50**
 FORK SUSPENSION TRAVEL: **180 mm**
 SIZE BRAKE DISC: **203 mm front**
203 mm rear
 ENGINE: **BOSCH Performance Line CX**
 BATTERY: **BOSCH PowerTube 625Wh**

Because of the problems in the delivery chain arising from the current COVID-19 situation, the bike can be delivered with modifications.