



Datasheet E-Power iLink 180 Race

For more informations visit www.corratec.de

iLINK 180

E-Power iLink 180 Race

Frame: Corratec E-Power iLink 180 Boost

Components: Sram NX Eagle

Size: 42, 48, 52

Colors:



TECHNOLOGIES



DESCRIPTION

- Ultralight carbon frame including carbon - rear triangle with 180mm travel.
- A downhill machine that ensures amazing pleasure on all trails of the world.
- Shadow Edge Tube 3.0 - worldwide most stable and safest corratec E-Bike frame.

FRAME

CM	A	B	C	D	E	F	G	H
42	599	86	65	77	1236	445	455	616
48	611	97	65	77	1248	445	465	621
52	623	106	65	77	1262	445	475	629

EQUIPMENT

MAIN:

FRAME:	Corratec E-Power iLink 180 Boost
FORK:	Rockshox Yari RC 29"
FULLY DAMPER:	Rockshox Super Deluxe Select
BRAKES:	SRAM Guide front SRAM Guide T rear
STEM:	ZZYZX SL Alloy
HANDLEBAR:	ZZYZX SL Alloy Handlebar
SADDLE:	Selle San Marco Gnd Full-fit
SEATPOST:	Kindshock 900i

DRIVE:

CHAINWHEEL:	SRAM X-SYNC 2 34T
CASSETTE:	SRAM CS PG1210 11-50T
REAR DERAILLEUR:	SRAM GX Eagle Lunar 12S
SHIFT LEVERS:	SRAM NX Eagle Single Click

WHEELSET:

RIM:	ZZYZX X30 front ZZYZX X30 rear
TIRE:	Michelin E-Wild 29 front Michelin E-Wild 650B rear

SPECIAL:

CHAINWHEEL RATIO:	1s; 34
CASSETTE RATIO:	12s; 11 13 15 17 19 22 25 28 32 36 42 50
FORK SUSPENSION TRAVEL:	180 mm
SIZE BRAKE DISC:	203 mm front 203 mm rear
ENGINE:	BOSCH Performance CX Race
BATTERY:	BOSCH PowerTube 625Wh
ACCESOIRES:	Bosch Kiox 300 Display

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications.

Rendering is for Reference only.