



Datenblatt Revo BOW SL PRO

Weitere Informationen finden Sie auf der Homepage www.corratec.de

REVO BOW

Revo BOW SL PRO

Rahmen: Corratec BOW SL Carbon 29" 12x148mm

Größe: 39, 44, 49, 54

Farben:



TECHNOLOGIEN



BESCHREIBUNG

- BOW frame geometry for exceptional self-damping and comfort.
- Popular, mechanical Shimano XT/SLX 12-speed drivetrain., ideal for tackling steep climbs.
- RockShox SID Select for maximum control and optimal traction.

RAHMEN

AUSSTATTUNG

BASIS:

RAHMEN:	Corratec BOW SL Carbon 29" 12x148mm
GABEL:	ROCK SHOX SID SELECT RL 29" 15x110mm 10 0mm
BREMSEN:	SHIMANO SLX BR-M7120 4-Piston 180mm vorne SHIMANO SLX BR-M7100 2-Piston 160mm hinten
VORBAU:	ALLOY 31.8mm 80-90mm -10 Deg
LENKER:	CARBON 31.8 750mm 6 Deg Backsweep
SATTEL:	SELLE ITALIA MODEL X
SATTELSTÜTZE:	CARBON TWIN BOLT 31.6x400mm

ANTRIEB:

KURBEL:	SHIMANO FC-M7100-1 SLX 175MM 32T
KASSETTE:	SHIMANO CS-M7100-12 SLX 12-SPEED 10-51 T
SCHALTWERK:	SHIMANO RD-M8100 XT SGS 12-SPEED
SCHALTHEBEL:	SHIMANO SL-M7100-R SLX RIGHT 12-SPEED

LAUFRAD:

FELGE:	DT SWISS M 1900 SPLINE® 29" 30 mm Disc CL Tubeless Microspline vorne DT SWISS M 1900 SPLINE® 29" 30 mm Disc CL Tubeless Microspline hinten
REIFEN:	Schwalbe RACING RAY Perf 57-622 B/B HS489 ADDIX 67EPI vorne Schwalbe RACING RALPH Perf 57-622 hinten

SPEZIAL:

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications. Rendering is for reference only.