



Datasheet Revo BOW ILINK PRO

For more informations visit www.corratec.de

REVO BOW

Revo BOW ILINK PRO

Telaio: Corratec Revo Bow iLink Carbon 29" 100mm

Travel 12x148mm

Dimensione: M, L, XL

Colori:



TECNOLOGIE



WHEEL
SIZE



DROPPER
POST



THROUGH
AXLE

DESCRIZIONE

- Your New trail companion.
- Enjoy the popular mechanical Shimano XT 12-speed shifting.
- Feel the balanced choice of reliable components.

TELAIO

ALLESTIMENTO

PRINCIPALE:

TELAIO:	Corratec Revo Bow iLink Carbon 29" 100mm Travel 12x148mm
FORCELLA:	ROCK SHOX SID BASE 3 POS 29" 15x110 120 mm
FRENI:	SHIMANO XT M8120 4/2-Piston 180mm anteriore SHIMANO XT M8100 4/2-Piston 180mm posteriore
ATTACCO:	ALLOY 31.8mm 60mm -3 Deg
MANUBRIO:	ALLOY 31.8mm 760mm 9 Deg Backweep 20mm Rise
SELLA:	SELLE ITALIA; X3 XP BOOST Superflow
REGGISELLA:	KS RAGEI 31.6 125mm

RUOTE:

CERCHIO:	DT SWISS XM1700 SPLINE® 29" 30 mm Disc CL Tubeless Microspline anteriore DT SWISS XM1700 SPLINE® 29" 30 mm Disc CL Tubeless Microspline posteriore
PNEUMATICO:	Schwalbe Nobby Nic Performance Addix 62-62 2 SELLE ITALIA X3 anteriore Schwalbe Nobby Nic Performance Addix 62-62 2 SELLE ITALIA X3 posteriore

TRASMISSIONE:

GUARNITURA:	SHIMANO FC-M8100-1 DEORE XT 175MM 32T
CASSETTA:	SHIMANO CS-M7100-12 SLX 12-SPEED 10-51 T
DERAGLIATORE POSTERIORE:	SHIMANO RD-M8100 XT SGS 12-SPEED
LEVE DEL CAMBIO:	SHIMANO SL-M8100 DEORE XT 12-SPEED

SPECIALE:

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications. Rendering is for reference only.