



Datasheet Revo BOW SL FACTORY

For more informations visit www.corratec.de

REVO BOW

Revo BOW SL FACTORY

Telaio: Corratec BOW SL Carbon 29" 12x148mm

Dimensione: 39, 44, 49, 54

Colori:



TECNOLOGIE



DESCRIZIONE

- Ultra-light carbon frame with race geometry, designed to win races
- Electronic SRAM AXS shifting for precise gear changes even in the mountains.
- Race-tested DT Swiss wheelset for maximum stability.

TELAIO

ALLESTIMENTO

PRINCIPALE:

TELAIO:	Corratec BOW SL Carbon 29" 12x148mm
FORCELLA:	ROCK SHOX SID SL ULTIMATE 3 POS 29" 15x110 100mm
FRENI:	SRAM LEVEL ULTIMATE STEALTH 2-Piston 180 mm anteriore SRAM LEVEL ULTIMATE STEALTH 2-Piston 160 mm posteriore
ATTACCO:	URSUS MAGNUS HX.01 MTB integrated 75/85 mm
MANUBRIO:	URSUS MAGNUS HX.01 MTB integrated 760mm
SELLA:	SELLE ITALIA FLITE BOOST SUPERFLOW Carbon
REGGISELLA:	CARBON TWIN BOLT 31.6x400mm

RUOTE:

CERCHIO:	DT SWISS XRC 1200 SPLINE® 29" 25mm 6-bolt Tubeless XD anteriore DT SWISS XRC 1200 SPLINE® 29" 25mm 6-bolt Tubeless XD posteriore
PNEUMATICO:	Schwalbe RACING RAY Evo 57-622 anteriore Schwalbe RACING RALPH Evo 57-622 posteriore

TRASMISSIONE:

GUARNITURA:	SRAM FC XX SL EAGLE Q168 CL55 DUB 170 34 T-TYPE
CASSETTA:	SRAM CS XS 1299 T-TYPE 10-52T
DERAGLIATORE POSTERIORE:	SRAM XX SL EAGLE AXS T-TYPE 12-SPEED
LEVE DEL CAMBIO:	SRAM AXS POD ULTIMATE BRIDGE W/MMX

SPECIALE:

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications. Rendering is for reference only.