



# Datasheet Revo BOW SL PRO

For more informations visit [www.corratec.de](http://www.corratec.de)

## REVO BOW

### Revo BOW SL PRO

Telaio: Corratec BOW SL Carbon 29" 12x148mm

Dimensione: 39, 44, 49, 54

Colori:



#### TECNOLOGIE



#### DESCRIZIONE

- BOW frame geometry for exceptional self-damping and comfort.
- Popular, mechanical Shimano XT/SLX 12-speed drivetrain., ideal for tackling steep climbs.
- RockShox SID Select for maximum control and optimal traction.

#### TELAIO

#### ALLESTIMENTO

#### PRINCIPALE:

TELAIO:	<b>Corratec BOW SL Carbon 29" 12x148mm</b>
FORCELLA:	<b>ROCK SHOX SID SELECT RL 29" 15x110mm 10 0mm</b>
FRENI:	<b>SHIMANO SLX BR-M7120 4-Piston 180mm anteriore</b> <b>SHIMANO SLX BR-M7100 2-Piston 160mm posteriore</b>
ATTACCO:	<b>ALLOY 31.8mm 80-90mm -10 Deg</b>
MANUBRIO:	<b>CARBON 31.8 750mm 6 Deg Backsweep</b>
SELLA:	<b>SELLE ITALIA MODEL X</b>
REGGISELLA:	<b>CARBON TWIN BOLT 31.6x400mm</b>

#### TRASMISSIONE:

GUARNITURA:	<b>SHIMANO FC-M7100-1 SLX 175MM 32T</b>
CASSETTA:	<b>SHIMANO CS-M7100-12 SLX 12-SPEED 10-51 T</b>
DERAGLIATORE POSTERIORE:	<b>SHIMANO RD-M8100 XT SGS 12-SPEED</b>
LEVE DEL CAMBIO:	<b>SHIMANO SL-M7100-R SLX RIGHT 12-SPEED</b>

#### RUOTE:

CERCHIO:	<b>DT SWISS M 1900 SPLINE® 29" 30 mm Disc CL</b> <b>Tubeless Microspline anteriore</b> <b>DT SWISS M 1900 SPLINE® 29" 30 mm Disc CL</b> <b>Tubeless Microspline posteriore</b>
PNEUMATICO:	<b>Schwalbe RACING RAY Perf 57-622 B/B HS489</b> <b>ADDIX 67EPI anteriore</b> <b>Schwalbe RACING RALPH Perf 57-622</b> <b>posteriore</b>

#### SPECIALE:

Due to worldwide problems in the delivery chains, the bike can be delivered with modifications. Rendering is for reference only.